

Index

- 1 dB compression point 462
- 1/f current noise 795
- 1/f noise 531, 729, 731
 - GaN FETs 550
 - density spectrum 557
 - slope γ of 557
- 1kBT current 660
- 2DEG, average position of 365
- 2kBT current 660
- 3 dB compression point 462

- a**
- abrupt heterojunctions 651
- absorption 8
 - coefficient 7, 10, 205, 216, 217, 224, 733, 792
 - process 8, 172, 197, 204, 206
 - rate 216
- access regions 421
- activation energy 317, 514, 795
 - characteristic 324
 - degradation 317
- advanced design system (ADS) 447
- aggregation 144
- aging test results 322
- Airy function 365
- AlGaN detectors 801
 - heterojunction 796
- AlGaN/GaN
 - HFETs 378, 463
 - interface charge 378
 - modulation-doped field effect transistor 354
 - MQW photodetectors 806
 - sheet charge calculation 672
- AlGaN/GaN interface charge 378
- AlGaN Schottky barrier photodiodes 780
 - spectral response of 780
- AlInN/AlN/GaN 2DEG channel 606, 607, 608
- AlInN barrier 606
- all-dielectric mirror cavity 302
- ambipolar diffusion coefficient 744
- amplifier classification 458
- analytical device modeling 419
- angled sidewall 22
- anharmonic interaction(s) 581, 582, 587
- anharmonic lifetime 603
- anharmonic phonon decay 582
- anomalies 497
- anomalous gain 786
 - characteristics 498
- apparent activation energy 514
- apparent capture cross section 514
- applied bias 719
- areal thermal generation-recombination 731
- areal trap density 506
- Arrhenius plot 619, 620
 - mean time failure 620
- atmospheric detection range 751
- atmospheric layers 747
- atmospheric transmission 748
 - UV transmission 748
- atomic nuclei 539
- Auger recombination processes 76, 78, 79, 249
 - coefficient 76, 77
 - rate 80
- available noise power 535
- available power gain (G_A) 412, 413
- avalanche breakdown voltage 486
- avalanche coefficients 537
- avalanche ionization 621
- avalanche multiplication 811
- avalanche noise 536

avalanche photodetectors 810, 811
 avalanche photodiodes (APDs) 717
 average velocity 650

b

backlight configuration 117
 bactericidal action 711
 ballistic transport 651
 bandgap narrowing 654
 bandgap reduction 238
 bandgap renormalization 237, 238, 261
 band structure 392, 393
 band tails 68
 band-to-band radiative recombination 80
 barrier height 642
 barrier lowering process
 – Poole–Frenkel effect 519, 520
 barrier states
 – current anomalies effect 509
 base-collector 637
 base transit time 648, 650, 654, 655
 beam intensity 202
 biaxial strain 242, 243
 bipolar transistors 662
 – noise 662
 blackbody emissivity 755
 blackbody radiator 535
 black dots 325
 Bloch functions 221
 blue phosphors 110
 Bohr radius 238
 Bose–Einstein condensation 308, 309
 boundary conditions
 – HBTs 642
 Bragg reflectors 55, 295
 breakdown voltage 487, 494, 665
 – gate length dependency 491
 bremsstrahlung 539
 brightness 28
 broadening factor 228, 260
 broadening process 237, 238
 bulk current 790
 bulk degradation 324
 bulk polaritons 312
 BY_V approach 101

c

capture cross section of the trap 514
 capture/emission processes 511
 – balance of 511
 capture of electrons 507
 carbon contamination 321
 carbon layers 322
 carbon mapping 323

carrier confinement 213, 215
 carrier degeneracy 595
 carrier-density fluctuation model 557
 carrier diffusion model 670
 carrier-launching ramp 651
 carrier leakage 76
 carrier overflow 265
 carrier recombination 253
 – lifetime 263, 720
 carrier transit time 787
 case temperature 572
 catastrophic failure 616
 cavity length 280
 cavity losses 278
 cavity mode(s) 194, 199, 201
 – dispersion 310
 cavity photon effective mass 296
 cavity polaritons 312
 cavity thickness 295
 CCD 760, 761
 – CD-Rom (CD read only memory) 170
 CD-Rom player 171
 Cerenkov processes 610
 channel potential 371
 channel resistance (RC) 424
 – delay time constant 455
 – subcircuit 432
 – time constant 723
 channel temperature 618
 characteristic temperature 273, 275, 323, 325,
 326
 characteristic time 731, 795
 – constant(s) 731
 charge-transfer excitons (CTE) 143, 145
 charge transport 132
 charged trap 503
 charging delay plot 455
 chromaticity color coordinates 30, 31
 chromaticity diagram 31, 90
 cladding layers 11
 classical radius 551
 coherence parameter 551
 coherent quantum $1/f$ effect 540
 coherent quantum $1/f$ noise 554
 – spectrum 551
 coherent regime 652
 cold cathode fluorescent light bulbs 120
 cold conditions 424
 collapse-free operation 569
 collector-common-emitter output I - V
 characteristics 671
 collector-emitter offset voltage 646
 collector transit time 658
 colloids 112

- color matching functions 31
 - color-mixing efficiency 29
 - color rendering index (CRI) 42, 88, 89, 95, 98
 - general 88, 89
 - special 88
 - color temperature 30, 31
 - collisions mean free path 813
 - Combining LEDs and Phosphor(s) 100
 - Commission Internationale de l'Éclairage (CIE) 27
 - common-base *I-V* characteristics 669
 - common-emitter current gain 644
 - compact disk (CD) 170
 - compact disk read only memory (CD-ROM), player 170, 171
 - compositional fluctuations 253
 - compositional gradient 654
 - compositional grading 653, 654
 - compositional strain inhomogeneities 252
 - computational method 747
 - plexus 747
 - conditional stability 416
 - conduction band discontinuity 639
 - conduction band edge 390, 396
 - conduction band profile 364
 - Cones 23, 24
 - confinement factor 186, 190, 194, 195, 260, 301
 - contact degradation 324
 - continuity equation 4, 718, 736
 - contrast parameter 256
 - conventional quantum $1/f$ 554
 - coefficient 551
 - effect 538
 - noise 552
 - noise parameter 550
 - noise spectrum 551
 - coordinate diagram configuration 507
 - coplanar waveguides (CPW) 408
 - conductor-backed 409
 - correlated color temperature (CCT) 32, 88, 89, 95, 104
 - correlation coefficient 544, 560, 664
 - Coulomb effect(s) 235, 250
 - Coulomb hole contribution 237, 238
 - Coulombic interaction 237, 248, 252
 - Coulombic processes 247
 - Coulombic-type trap 517
 - Coulomb interaction 249
 - Coulomb potential 541
 - critical angle 8, 181
 - loss 8
 - critical loss efficiency 8
 - cross-correlation spectrum 547
 - cross talk 327
 - cumulative conventional quantum $1/f$ coefficient 553
 - cumulative failure rates 619
 - current collapse 497, 498, 508, 525, 526, 528
 - current confinement structure 302
 - current crowding 11
 - current density equations 718
 - current dependent spectra 67
 - current gain cutoff frequency 417, 454, 456, 473, 638
 - current gain(s) 643, 659, 661, 663
 - DC current gain 663
 - forward/reverse 643
 - high currents 661
 - current lag 498, 499, 500, 528, 565
 - buffer traps effect 500
 - current noise spectrum 547
 - current/power gains 471
 - current response 718
 - current-spreading length 13
 - current transport mechanism 639, 648
 - across base 648
 - across heterojunction 639
 - Curtice-cubic model 439, 441, 448
 - Cutoff frequency 454
- d**
- dark conductivity 738
 - dark current(s) 778, 790, 793, 812
 - density 766
 - dark lines 325
 - defects (DLDs) 319
 - dark resistance 782
 - data transfer rate 172
 - Davydov splitting 136, 144
 - de Broglie wavelength 642
 - Debye model 583
 - decorative lighting 83
 - deembedding 417
 - deep UV radiation/detection 744
 - defect-assisted tunneling processes 778, 784
 - defect mapping 520
 - degeneracy effects 631
 - degradation 70
 - degradation rate 317, 324
 - delay time 265
 - density-of-states 200, 222, 223, 225
 - 1D 223
 - 2D 223, 232
 - joint 224, 225
 - depletion layer 640
 - width 732

- detectivity 738, 739, 741, 817
 - background radiation limited case 741
 - thermal noise 803
 - detector dark current 732
 - detector resistance 719
 - determinant 416
 - dielectric function, complex 181
 - differential gain 263
 - differential push-pull 328
 - differential quantum efficiency 267
 - differential resistance 730, 803
 - diffusion coefficients 718
 - diffusion constants 724
 - diffusion current 723
 - diffusion fluctuation 543
 - diffusion length 724
 - diffusion limit 652
 - diffusion-limited diode 723
 - diffusion model 642
 - direct-bandgap semiconductor
 - optical transitions 209
 - direct tunneling 510
 - dispersion relation 199
 - upper/lower polaritons 311
 - dispersion/temperature effects 447
 - distributed Bragg reflectors (DBRs) 55, 295, 297
 - crack-free 297
 - mirror 297, 300
 - penetration depth 296
 - reflectivity 297, 300
 - distributed losses 196
 - doping graded base 639
 - doping induced grading 653
 - double-heterojunction bipolar transistors 641
 - downward transitions rate 197, 203, 211
 - drain breakdown voltage 459, 483, 491
 - drain current 372, 373, 397
 - fluctuation 552
 - lag 567
 - transient(s) 515, 516, 522, 523
 - drain delay time 455
 - drain delay plot 456
 - drain efficiency 480, 498
 - drain feedback capacitance 561
 - drain saturation current 374
 - drain short-circuit noise current 561
 - drain-to-gate feedback capacitance 457
 - drain-voltage 483
 - drifting nonequilibrium phonons 594
 - drift velocity 600
 - DVD 170
 - DVD-ROM drives 170
 - DX centers 498
 - dynamic polarization 577
 - dynamic resistance 800, 803
- e**
- early (infant) failure 614
 - Ebers-Moll equations 644
 - Ebers-Moll model 644
 - effect of threading Dislocation 57
 - effective carrier velocity 580
 - effective diffusion coefficient 654
 - effective electron drift velocity 579
 - effective intrinsic carrier concentration 654
 - effective length 296
 - effective mass 209, 222
 - approximation 358
 - density-of-states 222
 - electron 209
 - hole 209
 - effective temperature 548
 - effective transit time 429
 - efficiency 7, 460, 736, 737
 - degradation 76
 - droop 76, 81
 - eigenenergy/wave function 364
 - eigenvalues 365
 - Einstein's coefficient 197, 203, 211, 218, 221
 - A coefficient 203, 211, 221
 - B coefficient 198, 220
 - elastic constants 377
 - elastic stiffness tensor 367
 - electrical displacement 361, 367
 - electric field 362, 365, 373
 - saturation point 373
 - electric field distribution 614, 615
 - electric power dissipation paths 631
 - electrical efficiency 28, 104
 - electroluminescent devices 62
 - electromagnetic energy 198
 - energy density 200
 - volume density 198
 - electromagnetic radiation 539
 - electromagnetic wave, intensity of 204
 - electromechanical coupling 366
 - electron-blocking layer 326
 - electron concentration 232
 - electron density distribution(s) 391, 392, 393, 396
 - electron diffusion current 724, 725
 - electron distribution 360, 364
 - electron-electron interaction 249
 - electron emission 519
 - electron energy relaxation time 633

- electron-hole pairs 641
 - electronic noise 531, 545
 - electron mobility 353, 791
 - electron occupancy 229
 - factor 226
 - electron-phonon coupling 592, 629
 - electron sheet charge 369
 - electron temperature 595
 - electron transport 353
 - electron transport layer (ETL) 126, 127, 131
 - electron tunneling, gate to surface 624
 - electron velocity-field characteristics 596
 - electron velocity overshoot 657, 658
 - electrothermal simulations 448
 - electrothermal subcircuit 449
 - emission coefficient 513
 - emission processes 204, 205
 - emission rate 217, 520
 - emitter–base junction 637
 - emitter current crowding effect 662
 - emitter injection efficiency 667
 - empirical methods 419
 - end loss 267
 - energy balance 202
 - energy-dependent capture cross section 555
 - energy relaxation time 543, 632
 - energy temperature 535
 - energy transport fundamentals 132
 - epitaxial lateral overgrowth (ELO) 270, 273
 - equilibrium phonon population 632
 - equivalent circuit models 417
 - cold condition at low frequency 426
 - zero gate bias cold condition at high frequency 426
 - equivalent noise conductance 559
 - equivalent noise current source 544
 - equivalent noise resistance 546, 559
 - equivalent noise temperature 535, 542
 - etched facet (mirror) technology 332, 333
 - lasers 333
 - excess carrier lifetime 719
 - excess electron concentration 773
 - excess hole concentration 723
 - excess noise 732
 - exciton oscillator strength 309
 - exciton phase-space filling density 247
 - exciton polariton dispersion 310
 - excitons pathways 246
 - expectation value, energy 366
 - expected two dimensional electron gas (2DEG)
 - position 366
 - extended line configuration 404
 - extended states 255
 - external noise source 549
 - external quantum efficiency (EQE) 29, 44, 81, 267, 733
 - extraction efficiency 28, 106
 - extraordinary refractive index 176
 - extreme-ultraviolet 709
 - extrinsic capacitance elements 425
 - extrinsic parameters 424
 - extrinsic resistances 428
 - extrinsic transconductance 375
 - eye diagrams 327
- f**
- Fabry–Perot frequency 296
 - facet damage 319
 - facets coating delamination 324
 - far-field pattern 191, 193, 195
 - far-ultraviolet 709
 - fast Fourier transform (FFT) 739
 - Fe doping 633
 - feedback capacitance 454
 - feedback resistances 432
 - Fermi’s golden rule 218
 - Fermi-Dirac distribution function 228, 360
 - Fermi-Dirac statistics 210
 - fiber-optic communications 3
 - field effect transistors (FET) degradation 612
 - field-assisted emission 516
 - field distribution 192
 - field emission Auger electron spectroscopy 322
 - field emission scanning electron microscope (FESEM) 322
 - field plates (FPs) 351, 464, 475, 485, 494, 495, 613, 621
 - figure of merit 722
 - filter loss 755
 - fine structure constant 540
 - finesse 306
 - finite element analysis (FEA) 571
 - flat panel displays 62
 - flicker characteristics 554
 - external quantum efficiency 45
 - flicker noise 732
 - flip-chip LED external quantum efficiency 45
 - flip chip LED (FCLED) 17, 44
 - flip-chip mount LED 46
 - flip chip-mounted heterojunction field effect transistors (HFET) 465
 - floating base phototransistor 809
 - focal plane arrays (FPAs) 714, 816
 - Fock space 540
 - focused ion beam 333
 - forward voltage transfer ratio 403
 - four-LED chips 91

- approach 98
 - four-level system 208
 - Fröhlich coupling 592, 604, 609
 - fractional quantum $1/f$ fluctuation 552
 - Franck-Condon (FC) shift 501, 506
 - Franck-Condon correction 502
 - Franck-Condon principle 141
 - Frenkel excitons 136
 - frequency-dependent noise 542
 - Fresnel loss 8
 - fudging parameter 554
 - full channel conductance 372
 - fundamental $1/f$ noise 538
- g**
- gain 175, 203, 205, 211, 236, 262, 263, 264, 401, 480
 - absorption spectrum 285
 - avalanche photodiode 812
 - broadening 238
 - expression 229
 - spectra 280, 284, 285
 - gain calculations 241
 - Wz GaN Q wells with strain 241
 - Wz Q wells without strain 241
 - gain coefficient 204, 233, 263, 284, 285
 - Gain in GaN photoconductive detector 770
 - gain in ZB Q wells, with strain 245
 - gain in ZB Q wells, without strain 244
 - gain measurement 257, 261
 - electrical injection 261
 - optical pumping 258
 - GaInNAs quaternary infrared lasers 312
 - GaN-based lasers 327
 - applications of 327
 - GaN HFET reliability 619
 - GaN HFETs performance 465
 - GaN MSM photodiodes 785, 787
 - responsivity dependence on bias 785
 - time response of 787
 - GaN photoconductive detector gain 770
 - GaN photoconductor 771, 792
 - responsivity of 771
 - spectral response of 792
 - GaN quantum wells gain 241
 - gated transmission line measurement (GTLM) 527
 - gate filling pulses 516
 - gate lag 499
 - gate leakage current 488, 490, 623
 - dependence on gate length 492
 - paths 623
 - gate leakage reduction 563
 - gate-source capacitance 454, 457
- Geiger mode 758, 812
 - gen III photodiode arrays 759
 - generation rate expression 719, 727, 731, 743
 - generation-recombination (G-R) 718
 - centers 729
 - current 727
 - noise 531, 533, 729, 731
 - generator reflection coefficient 548
 - graded base 639
 - green gap 86
 - green phosphors 110
 - group refractive index 201
 - Grüneisen's constant 587
 - Grüneisen's parameter 589
 - guidance condition 183
- h**
- H-aggregate 144
 - h -parameters 402
 - Hakki–Paoli method 281
 - half-wave plate 328
 - Hamiltonian 365
 - operator 218
 - interaction 218, 220
 - Handel's quantum $1/f$ cross-correlations 552
 - harmonic condition 220
 - heterojunction bipolar transistor (HBT) 352, 637, 649, 658
 - delay time 649
 - fundamentals 638
 - Gummel plot 670
 - nitride-based 665
 - heat dissipation 570
 - heat removal 269, 577
 - heat sink 576
 - Henry approach 284
 - heterointerface charge 356
 - heterojunction bipolar transistor 635, 636
 - heterojunction field effect transistors (HFETs) 349, 352, 369
 - AlGaIn/InGaIn 380
 - analytical description 369
 - GaN/InGaIn channel 375
 - InAlN barrier 609
 - InAlN/GaN 382
 - InAlN/InGaIn 384
 - InGaIn channel 609
 - insulating gate 570
 - large-signal 464
 - small-signal 464
 - heterojunction field effect transistors (HFET) amplifier 457
 - class A amplifier 457

- class AB amplifier 458
- class B amplifier 458
- class C amplifier 459
- class E amplifier 459
- efficiency 457
- heterojunction phototransistor(s), 808, 809
- higher lying triplet state 138
- highest occupied molecular orbital (HOMO) 126, 136
- high-forward gate current test (HFGC) 617
- high-frequency equivalent circuit 421
- high-frequency noise 541, 558
- high-resistivity GaN 633
- high-resolution lattice images 319
- high-temperature operating life test (HTOL) 617
- highly accelerated stress test (HAST) 617
- High-temperature reverse-bias test (HTRB) 617
- High-temperature storage test (HTS) 617
- hole concentration 233
- hole diffusion current 724, 725
- hole injection 640
- hole mobility 791
- hole occupancy 229
 - factor 226
- hole-transporting molecules (HTMs) 131
- hole transport layer (HTL) 125, 127
- holographic optical element 328
- Hooge parameter 554, 556, 732
 - α_H 551
 - α_K 554
- hopping conductivity 732
- hot carrier relaxation 596
- hot electron energy relaxation time 605, 606
- hot electron fluctuations 542
- hot electron noise 541, 542
 - temperature 535, 542
- hot electrons 531, 578
- hot field effect transistors operating conditions 429
- hot modeling 423
- hot optical phonon 578
- hot phonon lifetime 588, 607
 - dependence on electron concentration 593
- hot phonons 578, 579, 629, 631
 - depopulation 582
 - effects 577
 - implications for FETs 593
 - induced friction 603
 - phonon temperature 598, 599, 607, 632
 - population 632
- hot UV-emitting object 756

i

- IC-CAP 447
- ideality factor 660
- IG vs. VG 623
- impact ionization 508
 - current 641
- impedance matrix 401
- impulse response technique 657
- InAlGaNS SQW laser 292, 293
 - *L-I* curve 293
 - spectrum for 293
- In/AlGaN 53
- InAlN barriers 611
- In in AlGaN 53
- incident power 718
- incremental (differential) diode resistance 721
- inductances 428
- infant failure 616
- infrared catastrophe 539
- inhomogeneities 286
- injection efficiency 265
- injection lasers analysis 263
- in-plane strain 377, 381, 386
- in-plane wave vector 296
- interface charge 383, 385, 370
 - due to dopants 380
- interfacial trapping 779
- internal conversion, OLEDs 143
- internal loss 194, 267
- internal photogenerated charge profile 733
- internal quantum efficiency (IQE) 28, 81, 104, 267
- International Commission on Illumination (CIE) 27
- intervalley scattering 542, 652
- intrinsic capacitances 429
- intrinsic delay time 454
- intrinsic part 421
- intrinsic resistances 429
- ionization coefficient(s) 492, 665, 813
- ionized donor states 499
- isothermal current 450
- isothermal model 450
- I-V* characteristics numerical calculations 398

j

- J*-aggregates 144
- Johnson-Nyquist noise 531, 534, 664, 714, 729, 730, 817
- joint density of states (JDOS) 175, 233
- junction temperature 460, 570, 571, 575

k

- Kelvin probe 520, 521
 - kink, *I-V* characteristics 498
 - Kirk effect 661
 - Klemens' channel(s) 582, 583, 590, 592
 - Klemens phonon decay 585
 - knee voltage 459
- l**
- Lambertian design 19
 - landscape lighting 83
 - large signal characteristics 473, 475
 - large-signal equivalent circuit model 434, 437, 438, 453
 - HFET 438
 - laser annealing(LA) phonon group velocity 591
 - laser degradation 315
 - laser evolution 330
 - laser holography 21
 - lasers principles 172
 - LASIMO 447
 - lattice coordination diagram 498
 - lattice distorting defects 498
 - layer laser structure 272
 - leakage current 326, 729, 742
 - leakage resistances 779
 - lifetime 265, 279, 288
 - anharmonic 603
 - broadening 296
 - excess carrier 719
 - laser diode 316
 - minority carrier 724, 791
 - recombination 263, 264, 266, 720
 - light box 97
 - light emission 621
 - gate edge 621
 - OLEDs 139
 - light-emitting diodes (LEDs) 2, 3
 - Amber 47
 - blue 40
 - degradation 70
 - efficiency 76
 - fiber-optic 3
 - four-chip white light 17, 46, 97
 - green 40
 - laser 114
 - monochrome applications 2, 82
 - sapphire substrates 38
 - Si substrates 60, 61
 - SiC substrates 60
 - organic/polymeric 122
 - phosphor conversion 33
 - photon-recycling semiconductor (PRS-LEDs) 111, 113
 - resonant cavity-enhanced 55
 - superradiant devices 3
 - surface emitters 3
 - thin-film 19
 - thin-film flip-chip (TFFC) 84
 - three-chip white-light 91, 94
 - two 93
 - utilizing rare earth transitions 61
 - UV 48, 53
 - white light from Four-Chip 97
 - light-emitting polymers (LEPs) 52
 - light receptors 22
 - light-voltage vs. current characteristics 274
 - lightly doped collector 636
 - line broadening 236
 - line, reflect, reflect, match (LRRM) 409
 - linewidth broadening 228, 249, 591
 - LINMIC design suite 447
 - liquid crystal display (LCD) 116, 117
 - TVs 119
 - load line 462
 - load resistance 787
 - localization effects 66, 67
 - localized states 246, 251, 252, 253, 255, 732
 - localized states pathways 246
 - longevity performance 613
 - longitudinal-mode spacing 196
 - longitudinal optical (LO) 542
 - phonon absorption 542
 - phonon decay channels 584
 - phonon decay mechanism 593
 - phonon population 586
 - phonons 578
 - phonon to LA phonon decay 571
 - Lorentzian spectrum 795
 - losses 7
 - loss modes 194
 - low-energy X-ray spectral region 709
 - lowest unoccupied molecular orbital (LUMO) 126, 136
 - low-frequency noise ($1/f$ noise) 531, 537, 714
 - low-noise amplifiers (LNAs) 478
 - low-pass filter 731
 - luminance 28
 - luminescence conversion 85
 - luminous efficacy 26, 29, 98, 104
 - luminous efficiency 28, 45
 - luminous energy 28
 - luminous flux 28
 - luminous intensity 28

m

matched gain 415
 Materka–Kacprzak model 441
 matrix element 218
 Maury load-pull system 496
 maximum available gain 415
 maximum electron drift velocity 608
 maximum gain 231
 maximum luminous efficacy of radiation 29
 maximum oscillation frequency 456, 638
 maximum power conditions 415
 maximum stable gain (MSG) 416
 maximum transconductance 374
 mean power dissipation 596
 mean square photocurrent 731
 mean thermal velocity 642
 mean time to failure (MTTF) 288, 619
 mechanical, electrical, and thermal energies
 pathways 630
 metal-semiconductor-metal (MSM) 717, 782,
 788
 – AlGaN photodiodes 785
 – detector 783
 – frequency domain response 788
 – GaN detectors 783
 – photodetector 784
 – time domain response of 788
 metal-oxide semiconductor FET
 (MOSFET) 349
 metal-semiconductor field effect transistors
 (MESFET) 349
 microcavity (MC) lasers 295
 microchannel plate (MCP) 758, 761
 microplasma breakdown 811
 mid-ultraviolet 709
 mini disk 328
 minimum noise figure 476, 548, 559, 562
 minority carrier injection 638
 mirror reflectivity 295
 mobility fluctuation model 557
 mobility fluctuation theory 732
 modal gain 281–283
 modes 200, 201
 – density 200
 – hopping 287, 288
 – number of 200, 201
 – spacing 280
 MODFET 350
 momentum matrix element 231
 momentum operator 230
 momentum relaxation time 543
 momentum vector 200
 Monte Carlo calculation(s) 580, 593, 594, 600,
 602, 603, 632, 633

Monte Carlo environment 587
 Monte Carlo method 579, 594
 Monte Carlo model 601
 Monte Carlo simulation 543, 589, 594, 595,
 596, 606, 607, 608, 609, 631, 657
 multichip SSL-LEDs 92
 multiple defects 319, 320, 321
 multiplication factor 537
 Munsell samples spectra 89

n

National Institute of Standards and Technology
 (NIST) 409
 near/far-field patterns 22
 near-ultraviolet 709
 net modal gain 263
 neurotransmitter 25
 NIST TRL 409
 nitride-based detectors 767
 – back-illuminated 717
 nitride LED light emission, its genesis 64
 nitride LED performance 37
 noise bandwidth 817
 noise, circuit description of 545
 noise current source 545, 663
 noise detectors 729
 noise equivalent circuit 544, 546, 663
 – BJT 663
 noise equivalent irradiance (NEI) 816, 817
 – solar blind detector 818
 noise equivalent power (NEP) 738, 739, 777,
 798
 – background radiation limited case 741
 – in shot noise dominated detector 740
 noise figure 482, 546, 547
 noise-matching conditions 547, 548
 noise measurements under forward bias 795
 noise measurements under illumination 796
 noise power 793
 – unit band 535
 noise spectra 537, 793
 noise spectral density 798
 noise temperature 605
 noise-to-signal ratio 546
 noise under reverse bias 793
 noise voltage source 545
 noisy admittance 545
 noisy impedance 545
 nonequilibrium phonons 587
 – distribution 594
 – populations 588
 nonequilibrium trapped charge 513
 nonfundamental $1/f$ noise 537, 538
 non injected facet (NIF) 321, 324

nonlinearities 436
 nonradiative multiphonon (NMP) 507
 nonradiative recombination 143
 nonradiative recombination time 6
 normalized responsivity 781, 782
 npn bipolar transistor 640
 numerical-aperture (NA) 172, 327
 numerical gain calculations 239
 Nyquist noise 531, 534, 729

o

occupancy fluctuations 555
 occupation probability 198, 210
 offset voltage 645
 organic light emitting diodes (OLEDs) 124,
 156
 – degradation 156
 – devices 146
 displays 151
 – lighting 155
 – transparent (TOLEDs) 128
 – white 147
 open channel conductance 505
 open-circuit noise voltage 544
 open-circuit photovoltage 719, 721
 open-loop configuration 117
 operating gain 412
 optical field (E field) distribution 186, 187,
 188, 189, 191, 193
 optical gain 196, 205, 260
 – bulk GaN 239
 – semiconductor approach 215
 – spectra 260
 optical generation rate (G_{op}) 731
 optical head element 329
 optical length 309
 optical losses 279
 optical power $P(\lambda)$ 767
 optical recording densities 327
 optical transition matrix 230
 optimum DC load resistance 461
 optimum generator reflection coefficient 548
 optimum source resistance 559
 ordinary refractive index 176
 organic crystals 135
 organic vapor-phase deposition 122
 out-of-band rejection ratio 755
 output I - V characteristics 375, 488
 output noise equivalent noise
 temperature 546
 output noise spectrum 546
 output power 474, 480
 oxygen mapping 323
 ozone layer 748

p

packaging 15, 110
 parasitic capacitances 421, 428
 parasitic resistances 426
 passivation 529, 530, 563
 passive display 153
 pcLEDs 101, 103, 104, 107
 peak gain 231
 peak junction temperature 574, 618
 peak voltage 621
 Perception of Visible Light and Color 22
 permittivity, tensor 367
 persistent photoconductivity (PPC) 714, 774,
 809
 phase-change 327
 phase trajectory 652
 Phillips laboratory expert-assisted user
 software (Plexus) 747
 phonon-assisted tunneling 510
 phonon decay 582
 – channels 581
 – time 581
 phonon dephasing 582
 phonon dispersion curves 583
 phonon emission time 589, 597
 phonon lifetimes 586, 589, 601
 – dependence on electron concentration 601
 phonon lifetime vs. electron density 604
 phonon occupancy factor 597
 phonon occupancy number 598, 813
 phonon population 595
 phonon relaxation time 597
 phosphor conversion LED (pcLED) 33
 photocathode 713
 photoconductive 713
 – detector 714, 719, 768
 – gain 719
 – lifetime 743
 – response 769
 photoconductor (PC) 719, 773
 – quantum efficiency 733
 – ultraviolet detectors 772
 photocurrent 718, 719, 721, 816
 – decay 774
 – density 736
 – time decay 799
 photodetector 743
 – bulk recombination 743
 – surface recombination 743
 photodiode arrays 815
 photodiode structures 715
 photoelectric current gain 719, 720
 photogenerated current density 735
 photoionization cross section 506

- photoionization energies 502
 photoionization spectrum 502
 photometry 27
 photomultiplier tube (PMT) 709
 – detectors 745
 photon absorption profile 792
 photon area 739
 photon-assisted tunneling 256
 photon conversion schemes 111
 photon density 201
 – per unit frequency 201
 – per unit volume 201
 photon energy 296, 718
 – density 198, 199
 – quanta 201
 photon extraction efficiency 104
 photon flux density 718
 photon-generated carriers 735
 photon-generated current density 736
 photon-mitigated carbon deposition 321
 photon mode density 200, 202
 photonic crystal(s) 21, 47
 photopic vision 26
 photoreceptors 23
 photorefections 734
 – internal 734
 – surface 734
 photoresponse 771
 – evolution 771
 photovoltage 721
 photovoltaic detectors 775
 – ultraviolet 772
 π -bonds 135
 piezoelectric charge(s) 381, 386
 piezoelectric coefficient(s) 253, 367
 – tensor 367
 Piezoelectric constants 377, 386
 piezoelectric-induced fields 253
 piezoelectric polarization 368, 376, 377, 387
 pigmentation 711
 pinch off voltage 372
 p-i-n-junction detectors 789
 planar cavity 296
 planar defects 319
 Planckian locus 31
 Planckian spectrum 86
 Planck–Nyquist formula 202, 203, 535
 Planck’s blackbody radiation distribution law 202
 plasmons 603, 604
 p-n-junction detector 720, 721, 734, 789
 – detectivity 742
 – noise 741
 – quantum efficiency 734
 p-n-junction diode 722
 – equivalent circuit 722
 Poisson’s equation 358, 361, 363, 504, 718
 polar longitudinal optical (LO) phonons 578
 polar optical phonon (POP) 601
 polariton lasers 308
 polarization vector 220
 polarizing beam splitter 328
 polyethylene terephthalate (PET) 129
 poly(para-phenylene vinylene) 127
 Poole–Frenkel constant 804
 Poole–Frenkel effect 510
 Poole–Frenkel emission 518
 population inversion 203, 206, 207, 211
 potential distribution 365
 potentially unstable 416
 potential spike 648
 power-added efficiency (PAE) 460, 461, 480
 power amplifiers 478
 power available 413, 414
 power dissipation 618
 – by a hot electron 632
 – by the LO phonons 597, 599
 power gain 412, 413, 414
 power, input-output 412
 power-matching conditions 547
 power performance 479
 power spectrum 539
 power vs. frequency 478
 Poynting vector 220
 preamplifier circuit noise 729, 817
 premature degradation 322
 pressure dependence of spectra 64
 proposed gate-surface leakage current mechanisms 624
 pseudomorphic MODFET 351
 pSpice (ORCAD) 447
- q**
- quality (Q) factor 302, 306
 quantum-confined stark shift 2
 quantum deficit 104
 quantum dots 66, 67, 112
 quantum efficiency 267, 719, 733, 737
 – definition 734, 735
 – external 719, 734, 737
 – internal 719, 737
 quantum mechanical electron tunneling 621
 quantum $1/f$ coefficient 552
 quantum $1/f$ noise 555
 quantum size effects 111
 quantum wells gain 231
 quarter-wave Bragg reflector 301

- quarter-wave plate 329
- quarter-wave stack 297
- quasi-Fermi levels 209, 212, 645, 647
- quasistationary eigenstates 312
- quaternary 52
- quiescent operating point 627

- r**
- R_0A product 722, 726
- Rabi splitting 309
- radiative current 262
 - density 235
- radiative linewidth 309
- radiative recombination time 6
- radiometry 27
- Raman shift 573
- random access memory (RAM) 171
- random failure 614
 - period 616
- rare earth transitions 62
- rate equation, semiconductors 210
- rate of change in population 198, 206
- Rayleigh–Ritz method 358
- reciprocal (symmetric) nonlinear device 424
- recombination coefficient 226
- recombination cross section 551
- recombination current 659
- recombination process 80
- recombination rate 264, 731
- red-emitting phosphors 110
- red phosphor 110
- reduced effective DOS 234
- reference impedance 411
- reference plane 404
- reflection coefficient(s) 196, 403, 404, 409, 410, 733
- reflections 8
- reflection spectra 300
- refractive index 176, 178, 180
 - AlGa_N 176
 - dispersion 178, 179, 201
 - distributions 188, 189, 193
 - Ga_N 176
 - InGa_N 180
- relaxation rates 579
- relaxation time approximation 543
- reliability 617, 624, 629, 633
 - gate current 624
 - hot electron/hot phonon issues 629
 - measurements 617
 - metallurgical issues 628
 - other issues 633
- responsivity 738, 739, 793
- retina 22, 23

- reverse injection 641
- reverse transfer ratio 404
- reversible failure 616
- red, green, and blue (RGB) all-LED array 117
- RF input signal 621
- RF output power 615
- RF stress 621, 622
- RG_CB approach 100, 101
- Richardson constant 642
- Richardson velocity 647
- ridge waveguide 276
- Ridley decay 585
 - channel 587
 - processes 592, 593
- Ridley's anharmonic process 591
- Ridley's channel 583, 590
- rods 23, 24, 26
- Rollett stability factor 415
- R_RRGB approach 101
- Rydberg energy 238

- s**
- saturation current 742
 - density 726
 - HBT 643
- saturation effects 258
- scanning Kelvin probe microscopy (SKPM) 522, 523
- scattering angle 578
- scattering efficiency 29
- scattering matrix 405
- scattering parameters 404
- Schottky barrier height 370
- Schottky photodiodes 776, 779
- Schrodinger's equation 358, 363, 365
- scotopic vision 26
- screened carrier exchange 238
- screening length 238
- self-heating 448, 631
- semiconductor lasers, glossary of 208
- semiconductors statistics 204
- semi-isotropic continuum model 587
- sheet carrier concentration 371
- sheet charge and current numerical modeling 389
- sheet charge density 393, 397
- sheet electron concentration 360
- Shockley–Read–Hall (SRH) recombination 718
- short-channel field effect transistors (FETs) 424
- short-circuited current gain 417
- short-circuit gate noise current 544
- short-circuit noise source 560

- short-circuit photocurrent 718
- short p-n-junction 724
- short, open, load, and thru (SOLT) 406
- shot noise 531, 532, 541, 664, 730
 - dominated photodetector 740
- SiC-based UV photodetectors 763, 764
 - silicon-based 763
- SiC photodiode 766
- SiC polishing 468
 - in H 468
 - in HCl 468
- sidewall deflector 22
- σ -bond 135
- signal photon flux 817
 - SiN passivation 528
- signal-to-noise ratio 738
- single-particle model 197
- singlet fission OLEDs 143
- Si read out IC 761
- slope efficiency 325
- slow electrons 652
- small-signal equivalent circuit 420, 664
 - HBT 664
 - modeling 420
- Snell's law 8
- solar-blind detector 800, 801
 - array 799
- solar-blind films 800
- solar-blind region 710
- solar-blind UV detectors 710
- solar erythema 711
- solar photons 753
 - inevitable losses 754
 - number 753
 - unavoidable losses 754
- solar radiation 749
 - spectrum 749
 - UV 746
- solar UV photons reaching lower altitudes, number of 749
- SOLT (SOLR) 409
- space charge current 727
- space charge region (SCR) 720
 - collector depletion region in spacer layer 392
- space layer inserted 392
- s-parameters 401, 402, 403, 405, 411
- specific detectivity (D^*) 712, 739
 - generation-recombination-limited case 740
- spectral density 201, 552, 730
 - conventional quantum $1/f$ fractional fluctuations 551, 553
 - function 731
- spectral distribution 202
- spectral gain 238, 239
- spectral intensity 535
- spectral noise densities 537
- spectral power distribution 93
- spectral response 789, 791
 - back illuminated solar blind photodiode 801
 - current 505
 - measurement setup 767
 - phototransistor 810
 - solar-blind detectors 802
- spectral steady-state responsivity 769
- spectrally integrated gain 286
- spectrum locus 31
- spontaneous emission 172, 173, 197, 199, 204, 206, 210, 216
 - factor 258
 - lifetime 198
 - rate 217, 218, 226, 227, 228, 235, 258
- spontaneous polarization 367, 368, 376, 378, 380, 381, 383, 386
- stacking sequence 319
- state-filling process 255
- states density 200, 221
- Statz model 441
- stimulated absorption 173, 198, 210
- stimulated emission 173, 197, 198, 199, 203, 206, 210, 215, 216, 259
 - process 202
 - rate 217, 227, 228
- Stokes shift 85, 86, 104, 110, 252
- storage capacity 172
- strain, tensor 367
- stratospheric ozone 745, 747
- stray capacitances 421
- stress tensor 367
- stress time-dependent I_{ds} - V_{ds} characteristics 626
- stress time-dependent I_{GS} vs. V_{ds} characteristics 626
- structure constant 540
- substrate thermal conductivity 460
- sudden failure 321, 613, 616, 634
- superluminescent devices 3
- superradiant devices 3
- surface charging 525, 526
- surface conduction model 625
- surface current 790
- surface donor states 357, 363
 - density of 363
- surface emitters 3
- surface leakage current 728
- surface potential 524, 525

- transients 523
 - surface processing 620
 - surface recombination 660
 - velocity 726, 791
 - surface states 362
- t**
- TE-mode 181
 - temperature dependence 448
 - coefficients 448, 665
 - spectra 67
 - temperature distribution 574
 - temperature effects 453
 - temperature-humidity bias test (THB) 617
 - temperature noise model (TNM) 549
 - test set 408
 - T-gate GaN-based FET 470
 - thermal conductivity 572, 577
 - thermal dissipation 572
 - thermal emission rate 513
 - thermal generation rate (G_{th}) 731
 - thermal ionization 506
 - thermal management 582
 - thermal noise 531, 534, 541, 548, 729
 - current 536, 537
 - limited detectivity 740, 797
 - mean square value 536
 - power 536
 - voltage 536, 537
 - thermal resistance 315, 575, 618
 - thermal velocity 651
 - thermal wall 570
 - thermionic diffusion theory 646
 - thermionic emission current 642
 - thermionic emission model 647
 - thermoluminescence (TL) 131
 - thin-film flip-chip 84
 - thin film LED 19
 - thin-film transistor (TFT) 123
 - third-order intermodulation 475
 - three-color approach 92
 - three-LED solution 93
 - three-level system 207
 - three temperature life test data 619
 - threshold condition 194
 - threshold current 262
 - density 206, 264
 - threshold gain 196, 205
 - threshold modes 194
 - threshold voltage 371
 - through, reflect, and line (TRL) 406
 - time-resolved Raman investigations 586
 - time response 798
 - top-emitting diode 46
 - total delay time 455
 - total efficacy 30
 - total junction current 726
 - total loss 194
 - total piezo-induced charge 387
 - total reflection 8
 - total sheet carrier density 394, 395
 - traffic light 82
 - transconductance 374, 429
 - dispersion 498
 - transducer power gain (G_T) 412, 413, 414
 - transfer matrix 401
 - transfer probability 141
 - transient current 517
 - transient simulation 508
 - transition rates, per unit volume 210
 - transit time 454, 656
 - transmission line matrix 656
 - transparency carrier concentration 260, 263
 - transparency condition 211
 - transparency current 264
 - transparency onset 175
 - transparent electrode 12
 - transport factor, forward/reverse 643
 - trap emission rate 512
 - trapped charge 515
 - trapping centers 499
 - trap-to-trap hopping mechanism 621, 622
 - triangular potential barrier 365
 - triangular well 369
 - trichromatic color-mixing approach 94, 106
 - tricolor phosphors 86
 - triphasphor blend 108, 109
 - blue emission spectra 109
 - UV emission spectra 109
 - triplet dynamics 140
 - tris-(8-hydroxyquinoline) aluminum (Alq₃) 125, 126
 - tristimulus values 31
 - TRL (LRL) 409
 - TRM (LRM) 409
 - tunneling current 728
 - tunnel junction 14
 - tunnel leakage 625
 - two-dimensional electron gas 350
 - two-level system 207
 - two-piece model 373
 - two-port network 401, 402, 403, 405, 406
- u**
- ultraviolet catastrophe 536
 - unconditional stability 416
 - uniaxial tensile strains 242, 243
 - unilateral gain, GTU 414, 415

- unitary amplifier 415
 - unity power gain frequency 456
 - unity step function (heavy side function) 553
 - universal intrinsic circuit 443
 - upward transition rate 197, 203, 211
 - UV absorption 747
 - UV imagers 814
 - UV photodetectors 762
 - Si-based 762
 - SiC-based 762
 - UV sensor optical aperture 755
 - UV sensors 709, 745
 - available 757
 - generation I (gen I) 709, 745
 - generation II (gen II) 709, 745, 758
 - generation III (gen III) 709, 745, 758, 759
 - misalignment 756
 - practical detection ranges 756
 - UV solar-blind detectors, design requirements 759
 - UV spectra 711
 - UVA spectra 711
 - UVB spectra 711
 - UV-visible contrast 768
- v**
- vacuum fluorescent displays 124
 - valence band discontinuity 639
 - Vallee–Bogani channel 583
 - vector potential 220
 - velocity field characteristics 581
 - velocity-field curves, several electron densities 602
 - velocity-field relationship 373
 - velocity fluctuations 544
 - velocity measurements 580
- vertical cavity surface-emitting laser 301
 - virtual gate 529, 621, 624
 - visible-light terminology 27
 - vitamin synthesis 711
 - voltage noise spectrum 547
 - voltage response 718
 - V-shaped defects 319
- w**
- wall-plug efficiency (power efficiency) 28, 106
 - wave equation 199
 - wave function 365
 - wave guiding 175
 - analytical treatment 180
 - modes 183
 - numerical solution 184
 - problem 180
 - wearout failure 614, 616
 - white-light generation 85, 91
 - application 114
 - approaches 91
 - history 114
 - white noise 731
 - Wiener–Khinchine theorem 533
- y**
- y-matrix 423
 - y-parameters 422, 423, 424, 425, 432
 - yttrium aluminum garnet (YAG) 90, 101
- z**
- zero-bias resistance 804
 - area product 797
 - zero resistance 726
 - zone-center LO phonon frequency 578
 - zone-center optical phonons 590

